



Member of the FM Global Group

FM Approvals
1151 Boston Providence Turnpike
P.O. Box 9102 Norwood, MA 02062 USA
T: 781 762 4300 F: 781-762-9375 www.fmaprovals.com

CERTIFICATE OF COMPLIANCE

HAZARDOUS (CLASSIFIED) LOCATION ELECTRICAL EQUIPMENT

This certificate is issued for the following equipment:

I. Load Cell Summing Junctions IS Version

Model a-bc-d, Load Cell Summing Junctions.

IS/I/1/ABCD/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; Entity
I/O/AEx ia/IIC/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; Entity

Entity Parameter values: Ui = 30 V, Ii = 100 mA, Ci = 0, Li = 0, Pi = 0.75 W

a = Enclosure: FP or SS
b = Type: 10, 30, 34, 40, 45, 65 or 85
c = Trim: AE or AS
d = Suppression: SP or None

Special Conditions of Use:

1. *Potential Electrostatic Charging Hazard – The enclosure is constructed from plastic. To prevent the risk of electrostatic sparking the plastic surface should only be cleaned with a damp cloth.*

II. Load Cell Summing Junctions IS Version

Model a-bc-d, Load Cell Summing Junctions.

IS/I/1/CD/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; System
I/O/AEx ia/IIB/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; System

a = Enclosure: FP or SS
b = Type: 10, 30, 34, 40, 45, 65 or 85
c = Trim: AE or AS
d = Suppression: SP or None

Special Conditions of Use:

1. *Potential Electrostatic Charging Hazard – The enclosure is constructed from plastic. To prevent the risk of electrostatic sparking the plastic surface should only be cleaned with a damp cloth.*

To assure that this Approval is still valid, please refer to www.approvalguide.com

III. Load Cells IS Version

Canister Model a, Load Cells.

IS/I,II,III/1/ABCDEFGH/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; Entity

I/O/AEx ia/IIC/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; Entity

Reference Control Drawing No. 1500-B-01 for Entity Parameter values

a = Type: CG-21, CG-26S, CG-26S1, CG-26S1-65114, CG-26S2, CG-26S3, CG-26S3-10, CG-26S4, CG-26S5, CG-26S6, CG-26S7, CG-31, CG-33, CG-62, CG-63, CG-92, CG-93, CG-94, CG-175, CG-412, CG-1210, CG-1210-1, CG-1211, CG-CC22, CG-CP22, CG-JRT, CG-SP9, CG-TC42 or CG-TC43

Double Ended Model a, Load Cells.

IS/I,II,III/1/ABCDEFGH/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; Entity

I/O/AEx ia/IIC/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; Entity

Reference Control Drawing No. 1500-B-01 for Entity Parameter values

a = Type: CG-16, CG-16-SSW, CG-58, CG-58-1, CG-5103, CG-5103-SSW, CG-5223, CG-5223-SSW, CG-80210, CG-BE40, CG-BE40-SSW, CG-BLC-2, CG-DB50000S, CG-Lodec, CG-ML600-LP, CG-ML1200, CG-SLS, CG-STR, CG-STR-1, CG-STR-1-SSW, CG-STR-SSW or CG-WBM

S Beams Model a, Load Cells.

IS/I,II,III/1/ABCDEFGH/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; Entity

I/O/AEx ia/IIC/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; Entity

Reference Control Drawing No. 1500-B-01 for Entity Parameter values

a = Type: CGSB, CGSB-1, CGSB-SS, CGSB-SSW, CSS10077, CSS10078 or CSS10079

Single Ended Beams Model a, Load Cells.

IS/I,II,III/1/ABCDEFGH/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; Entity

I/O/AEx ia/IIC/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; Entity

Reference Control Drawing No. 1500-B-01 for Entity Parameter values

a = Type: CG-23, CG-23-1, CG-23-LP, CG-23-SS, CG-23-SS-1, CG-23-SSW-XX, CG-8HL, CG-30410, CG-60030, CG-60040, CG-743, CG-745, CG-BBS, CG-BLC-C, CG-BLC-T, CG-BLF, CG-F1, CG-HMT, CG-LC22, CG-MBB, CG-MK15, CG-SB250, CG-SB2L, CG-SB2M, CG-SB3, CG-SB3-1, CG-SB4, CG-SBF, CG-SMB6, CG-SMB6-2, CG-SSB, CG-SSB-10, CG-TB2, CG-WBL-SS, CG-WB-SS, CG-Z6 or CG-Z6-1

Special Conditions of Use:

1. Enclosures containing aluminum constitute a potential risk of ignition by impact or friction. Care must be taken into account during installation and use to prevent impact or friction.

Single Points Model a, Load Cells.

IS/I,II,III/1/ABCDEFGH/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; Entity

I/O/AEx ia/IIC/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; Entity

Reference Control Drawing No. 1500-B-01 for Entity Parameter values

To assure that this Approval is still valid, please refer to www.approvalguide.com

a = Type: CG-22, CG-22-1, CG-22-2, CG-22-4, 3053177CG-40, CG-40-SS, CG-40-SS-1, CG-42, CG-42-1, CG-42-2, CG-50, CG-50-1, CG-50-SS, CG-50-SS-1, CG-50-2, CG-50-3, CG-51, CG-1010, CG-1130, CG-1130-1, CG-1240, CG-1240-SS, CG-1241, CG-1510, CG-60048, CG-60610, CG-65029, CG-FB, CG-FLS, CG-HPS, CG-MK21, CG-MK4, CG-MK5, CG-PB, CG-PB-1, CG-PWA, CG-PWA-1, CG-PWS, CG-SPL, CG-SPLM, CSS10115 or CSS10133

Special Conditions of Use:

1. Enclosures containing aluminum constitute a potential risk of ignition by impact or friction. Care must be taken into account during installation and use to prevent impact or friction.

IV. Load Cells IS Version

Canister Model a, Load Cells.

IS/I,II,III/1/CDEFG/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; System
I/O/AEx ia/IIB/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; System

a = Type: CG-21, CG-26S, CG-26S1, CG-26S1-65114, CG-26S2, CG-26S3, CG-26S3-10, CG-26S4, CG-26S5, CG-26S6, CG-26S7, CG-31, CG-33, CG-62, CG-63, CG-92, CG-93, CG-94, CG-175, CG-412, CG-1210, CG-1210-1, CG-1211, CG-CC22, CG-CP22, CG-JRT, CG-SP9, CG-TC42 or CG-TC43

Double Ended Model a, Load Cells.

IS/I,II,III/1/CDEFG/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; System
I/O/AEx ia/IIB/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; System

a = Type: CG-16, CG-16-SSW, CG-58, CG-58-1, CG-5103, CG-5103-SSW, CG-5223, CG-5223-SSW, CG-80210, CG-BE40, CG-BE40-SSW, CG-BLC-2, CG-DB50000S, CG-Lodec, CG-ML600-LP, CG-ML1200, CG-SLS, CG-STR, CG-STR-1, CG-STR-1-SSW, CG-STR-SSW or CG-WBM

S Beams Model a, Load Cells.

IS/I,II,III/1/CDEFG/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; System
I/O/AEx ia/IIB/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; System

a = Type: CGSB, CGSB-1, CGSB-SS, CGSB-SSW, CSS10077, CSS10078 or CSS10079

Single Ended Beams Model a, Load Cells.

IS/I,II,III/1/CDEFG/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; System
I/O/AEx ia/IIB/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; System

a = Type: CG-23, CG-23-1, CG-23-LP, CG-23-SS, CG-23-SS-1, CG-23-SSW-XX, CG-8HL, CG-30410, CG-60030, CG-60040, CG-743, CG-745, CG-BBS, CG-BLC-C, CG-BLC-T, CG-BLF, CG-F1, CG-HMT, CG-LC22, CG-MBB, CG-MK15, CG-SB250, CG-SB2L, CG-SB2M, CG-SB3, CG-SB3-1, CG-SB4, CG-SBF, CG-SMB6, CG-SMB6-2, CG-SSB, CG-SSB-10, CG-TB2, CG-WBL-SS, CG-WB-SS, CG-Z6 or CG-Z6-1

Special Conditions of Use:

1. Enclosures containing aluminum constitute a potential risk of ignition by impact or friction. Care must be taken into account during installation and use to prevent impact or friction.

Single Points Model a, Load Cells.

To assure that this Approval is still valid, please refer to www.approvalguide.com

IS/I,II,III/1/CDEFG/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; System
I/O/AEx ia/IIB/T4 -20 °C ≤ Ta ≤ +60 °C – 1500-B-01; System

a = Type: CG-22, CG-22-1, CG-22-2, CG-22-4, 3053177CG-40, CG-40-SS, CG-40-SS-1, CG-42, CG-42-1, CG-42-2, CG-50, CG-50-1, CG-50-SS, CG-50-SS-1, CG-50-2, CG-50-3, CG-51, CG-1010, CG-1130, CG-1130-1, CG-1240, CG-1240-SS, CG-1241, CG-1510, CG-60048, CG-60610, CG-65029, CG-FB, CG-FLS, CG-HPS, CG-MK21, CG-MK4, CG-MK5, CG-PB, CG-PB-1, CG-PWA, CG-PWA-1, CG-PWS, CG-SPL, CG-SPLM, CSS10115 or CSS10133

Special Conditions of Use:

1. *Enclosures containing aluminum constitute a potential risk of ignition by impact or friction. Care must be taken into account during installation and use to prevent impact or friction.*

To assure that this Approval is still valid, please refer to www.approvalguide.com

Equipment Ratings:

I. IS (Entity) Version

Intrinsically Safe Apparatus for use in Class I, Division 1 or 2, Groups A, B, C & D, in accordance with manufacturer's Control Drawing; Equipment protection by Intrinsic Safety for use in Class I, Zone 0, Zone 1, or Zone 2, AEx ia IIC, in accordance with manufacturer's Control Drawing, hazardous (classified) locations

II. IS (System) Version

Intrinsically Safe Apparatus for use in Class I, Division 1 or 2, Groups C & D, in accordance with manufacturer's Control Drawing; Equipment protection by Intrinsic Safety for use in Class I, Zone 0, Zone 1, or Zone 2, AEx ia IIB, in accordance with manufacturer's Control Drawing, hazardous (classified) locations

III. IS (Entity) Version

Intrinsically Safe Apparatus for use in Class I, Division 1 or 2, Groups A, B, C & D, Class II, Division 1 or 2, Groups E, F & G, Class III, Division 1 or 2, in accordance with manufacturer's Control Drawing; Equipment protection by Intrinsic Safety for use in Class I, Zone 0, Zone 1, or Zone 2, AEx ia IIC, in accordance with manufacturer's Control Drawing, hazardous (classified) locations

IV. IS (System) Version

Intrinsically Safe Apparatus for use in Class I, Division 1 or 2, Groups C & D, Class II, Division 1 or 2, Groups E, F & G, Class III, Division 1 or 2, in accordance with manufacturer's Control Drawing; Equipment protection by Intrinsic Safety for use in Class I, Zone 0, Zone 1, or Zone 2, AEx ia IIB, in accordance with manufacturer's Control Drawing, hazardous (classified) locations

FM Approved for:

Coti Global Sensors, Inc.
5699 Highway 53
Harvest, AL 35749
USA

To assure that this Approval is still valid, please refer to www.approvalguide.com

This certifies that the equipment described has been found to comply with the following Approval Standards and other documents:

Class 3600	2011
Class 3610	2010
Class 3810	2005
ANSI/ISA-60079-0	2013
ANSI/ISA-60079-11	2012
ANSI/ISA-61010-1	2012

Original Project ID: 3026213

Approval Granted: January 15, 2007

Subsequent Revision Reports / Date Approval Amended

Report Number	Date	Report Number	Date
3029958	June 25, 2008		
071010	July 3, 2008		
071013	August 22, 2008		
090204	May 29, 2009		
090825	November 12, 2009		
3040476	March 3, 2011		
110405	August 24, 2011		
120413	July 11, 2012		
121109	November 30, 2012		
3048686	June 27, 2014		

FM Approvals LLC



J.E. Marquedant
 Manager, Electrical Systems

27 June 2014
 Date

To assure that this Approval is still valid, please refer to www.approvalguide.com