

INSCALE™

UTILITY /DRUM SCALE



- **RUGGED**

100% Mig welded structural steel construction.

1/2" thick deckplate. 3" square live rails, on Domestic Scales

- **LOW PROFILE**

1" deck height and 8" long ramps permit easy access by handtrucks, carts, etc. on 30" x 30" platform.

- **SELF-CONTAINED**

No bolt-down required. Scale and ramps lock together to maintain alignment.

- **TRANSPORTABLE**

Three-piece design. Ramps and scale are transportable by handtruck. Relocation is accomplished without tools.

- **ACCURATE**

Utilizes four shear beam load cells. Meets or exceeds NIST H-44.

INSCALE™

UTILITY / DRUM SCALE

SPECIFICATIONS

INSCALE NUMBER	PLATFORM SIZE	SCALE CAPACITY	SHIPPING WEIGHT	NOMINAL HEIGHT OF DECK	OVERALL LENGTH	OVERALL WIDTH	LOAD CELL SIZE
30-30-IU	30" x 30"	1,000 lb.	200 lb.	1"	46"	36"	1K
33-2-IU	36" x 36"	2,000 lb.	300 lb.	1"	52"	42"	1K
44-5-IU	48" x 48"	5,000 lb.	425 lb.	2"	108"	54"	2.5K
45-5-IU	48" x 60"	5,000 lb.	475 lb.	2"	120"	54"	2.5K
46-5-IU	48" x 72"	5,000 lb.	52 lb.	2"	132"	54"	2.5K

FEATURES

Scale and Ramps are: Constructed of mild steel with checkered safety plate.

Painted: With Sherwin-Williams safety blue alkyd enamel

Scale Supplied: With 4- 1K or 2.5K shear beam load cells, and 15' indicator cable.

Safe Overload: 150% of rated capacity.

Safe Sideload: 100% of rated capacity.

Performance: Designed to meet or exceed — NIST H-44 for class III scales.

OPTIONS

Carbon or stainless steel.

Custom sizes. Precalibrated indicator. Smooth or diamond deck.

Distributed by: