



LP7510 WEIGHING INDICATOR



6-Digit 3/4" red LED display, w/ 13 indicators

Available in Stainless Steel

NTEP APPROVED AT 5000 DIVISIONS

Includes display indicator, AC adapter, instrument cable, RS232 adapter, housing and hardware, extra instrument cable end and NTEP certification hardware.

NTEP #09-070A1

Certificate of Conformance #09-070A1

STANDARD FEATURES

- Stainless Steel or Mild Steel Enclosure.
- 1" LED or LCD Display with backlight.
- Units (kg/lb) switchable.
- Mounting bracket and Hardware.
- NTEP approved for 5,000 divisions.
- Count, Auto Hold, Check Weighing features.
- Operates on 110V AC adapter.
- Full Duplex RS-232 Serial Port.
- Accuracy class 6000 e/30000D
- Drives up to 8 350Ω load cells.
- Ability to modify gravity based on different geographical locations
- Upper/lower limit alarm.
- Automatic power off and power save.
- Automatic error warning alarm.
- 100% manual zero range setting.
- Displays up to 50,000 graduations.
- Automatic date and time update.

SPECIFICATIONS

- Resolution display: 0, 000 ADC: 2,000,000
 - Zero stability error TKO < 0.1μV//K
 - Span stability error TKspn < ± 6 ppm//K
 - Conversion time 50 ms
 - Sensitivity (internal) 0.12 μV /count
 - AC power AC100~250V
 - DC power DC6V/4Ah rechargeable battery, 700mA
 - Operation temperature - 10 °C to 40 °C
 - Storage temperature - 40 °C to 70 °C
- Indicator Dimensions 7.87"(L) X 2.95"(W) X 7.17"(H)
Input voltage 5 VDC, 4 wire connection. Min. 50Ω, e.g.: 6 load cell of 350Ω



NTEP APPROVED

Includes display indicator, AC adapter, instrument cable, RS232 adapter, housing and hardware, extra instrument cable end and NTEP certification hardware.

Certificate of Conformance #09-070A1



LP7510 Indicator
Mild Steel Version

- #6508 / LP-7510 MILD STEEL, LED, NTEP
- #65085 / LP-7510 MILD STEEL, LED, W/ BATTERY, NTEP
- #650821 / LP-7510 MILD STEEL, LCD, W/ BATTERY, NTEP

LP7510 Indicator (Stainless Steel)
Stainless Steel Version

- #65082 / LP-7510-SS STAINLESS STEEL, LED, NTEP
- #65087 / LP-7510-SS STAINLESS STEEL, LCD, NTEP
- #650871 / LP-7510-SS STAINLESS STEEL, LED, W/ BATTERY, NTEP
- #65087U / LP7510-SS STAINLESS STEEL, LCD W/ BAT. / INT. POWER & CABLE
- #65087CU / LP7510SS-STAINLESS STEEL, LCD, W/ BAT. EXT. POWER

Additional parts/accessories

- #65088 / LP-7510 15' BRAIDED LEAD CABLE Q.D.
- #6508801 / LP-7510 30' BRAIDED LEAD CABLE Q.D.
- #65081 / LP-7510 A/C ADAPTOR